

MEDC 24 Hour Stock List

05/03/2010

Shipment of goods on the same day is normally guaranteed when orders are placed before 12 midday.
Please note that the quantities indicated are changing daily.
Contact MEDC prior to ordering, if short delivery time is required.
Please contact Sales department to place your order.
Tel: +44 (0) 1773 864100

ORDERING CODE	PRODUCT CODE	DESCRIPTION	STOCK LEVEL
BREAKGLASS CALLPOINTS			
		GRP, 2xM20 entries, Glass label Fire break glass, No features, 7 terminals, IP66 & 67	
PX800002	BGIB4B6B1DSN7R	Explosion protected, ATEX Approved Ex II 1GD, EExia, IIC, T4, Zones 0 / 1 & 2, dc, Single switch, Red finish	3
PX800003	BGEB4B6B1DSN7R	Explosion protected, ATEX Approved, Ex II 2GD, EExed, IIC, T6, Zone 1 & 2, dc, Single switch, Red finish	0
PX800004	BG2EDC1NR	Explosion protected, ATEX Approved Ex II 2GD, EExed, IIC, T6, Zone 1 & 2, dc, Single switch, Red finish	27
PX800005	BG2INN1NR	Explosion protected, ATEX Approved Ex II 1GD, EExia, T4, Zone 0 / 1 & 2, dc, Single switch, Red finish	4
PX800006	BG3W1NBR	Dust-tight & weather proof, Uncertified, 24V dc, Duty Label Burning House, Red finish	3
PX800007	BG311NBR	Explosion protected, ATEX Approved Ex II 1G, EExia, IIC, T4, Zone 0 / 1 & 2, dc, Single switch, Duty Label Burning House, Red finish	2
SOUNDERS			
		Alloy, ATEX Approved Ex II 2G, EExd, IIB, T4(T3), Zone 1 & 2, 2xM20 entries, IP66	
PX801001	DB1BA024A1A3NNNR	24v, dc, Choice of 6 tones, 103dB(A) output, Red finish	0
		GRP, 115dB(A), No labels, IP66 & 67	
PX803121	DB3PD048N2BPNN	ATEX Approved Ex II 2GD, EExd, IIC, T4, Zones 1 & 2, 12v-48v dc, Switchable two tone selection, 27 tones, Black finish, 2 x M20 Entries, C'd Plug	28
PX803122	DB3D240N2BPNN	ATEX Approved Ex II 2GD, EExd, IIC, T4, Zone 1 & 2, 240v ac, 27 tones, Black finish, 2xM20 Entries, Certified Plug	6
PX803123	DB3PD048N2BPNR	ATEX Approved Ex II 2GD, EExd, IIC, T4, Zone 1 & 2, 12v-48v dc, Switchable two tone selection, 27 tones, Red finish, 2xM20 Entries, Certified Plug	9
PX803124	DB3D240N2BPNR	ATEX Approved Ex II 2GD, EExd, IIC, T4, Zone 1 & 2, 240v ac, 27 tones, Red finish, 2xM20 Entries, Certified Plug	0
PX803125	DB3D048N2BPNR	ATEX Approved Ex II 2GD, EExd, IIC, T4, Zone 1 & 2, 12v-48v dc, 27 tones, Red finish, 2xM20 Entries, Certified Plug	11
		ABS, ATEX Approved Ex II 1G, EExia, IIC, T4, Zone 0 / 1 & 2, Choice of 26 tones, 103dB(A), IP65	
PX805001	DB5B012NR	12v dc, Up to 3xM20 entries via knockouts, No labels, Natural Red finish	4
PX805002	DB5B024NR	24v dc, Up to 3xM20 entries via knockouts, No labels, Natural Red finish	34
		GRP, 110dB(A) output, IP66 & 67	
PX807006	DB7PBB024NR	ATEX Approved Ex II 1G, EExia, IIB, T4, Zone 0 / 1 & 2, 24v dc, No labels, Choice of 26 tones, Red finish	4
PX808001	DB12P024NR	Dust-tight & Weatherproof, 24v dc, No Labels, choice of 27 tones, Red finish	0
PX808003	DB12115NR	Dust-tight & Weatherproof, 115/230v a.c., No Labels, choice of 27 tones, Red finish	4
		GRP, 117dB(A) output, 2 x M20 Entries, IP66 & 67	
PX808110	DB15P048NG	Dust-tight & Weatherproof, 24-48v dc, No labels, Choice of 27 tones, Grey finish	2
PX808115	DB15P048NR	Dust-tight & Weatherproof, 24-48v dc, No labels, Choice of 27 tones, Painted Red finish	2
PX808120	DB15240NG	Dust-tight & Weatherproof, 240v ac, Choice of 27 tones, Grey Finish	0
PX808125	DB15240NR	Dust-tight & Weatherproof, 240v ac, Choice of 27 tones, Painted Red Finish	2
SOUNDER/BEACON COMBI UNITS			
		GRP, ATEX Ex II 2GD, EExd IIB T5, Zones 1 & 2, 1 x M20 entry, IP66 & IP67	
PX803130	DB3/XB11B 24V RED/RED	24V dc, Choice of 27 tones, 115dB(A) Output, 29Cd, No labels, Red Lens, Red Finish	2
		GRP, ATEX Ex II 2G, EExde IIB T3, Zones 1 & 2, 1 x M20 entry + 1 x cert plug, IP66 & IP67	
PX803140	CU1SB024T06RNN2BPR	24V dc, Choice of 27 tones, 116dB(A) Output, 10 Joule, No labels, Red Lens, Red Finish	9
PX803141	CU1SPB024T06RNN2BPR	24V dc, Choice of 27 tones, two stage, 116dB(A) Output, 10 Joule, No labels, Red Lens, Red Finish	2
PX803142	CU1SB240T06RNN2BPR	240V ac, Choice of 27 tones, 116dB(A) Output, 10 Joule, No labels, Red Lens, Red Finish	0
SPEAKERS			
		GRP, ATEX Approved Ex II 2GD, EExd, IIC, T4, Zone 1 & 2, 100v Transformer	
PX804215	DB415DXN2BPN	15 watt, No labels, 2 x M20 entries with 1 certified plug fitted, Natural Black finish	1
PX804225	DB425DXN2BPN	25 watt, No labels, 2 x M20 entries with 1 certified plug fitted, Natural Black finish	6
		GRP, ATEX Approved Ex II 2G, EExde, IIB + H₂, T5/T6, Zone 1 & 2, 100v Transformer	
PX807908	DB10B8XN2BPN	8 watt (short flare), No labels, 2 x M20 entries with 1 certified plug fitted, Natural Black finish	2
PX807915	DB10B15XN2BPN	15 watt, No labels, 2 x M20 entries with 1 certified plug fitted, Natural Black finish	8
		GRP, Industrial & Marine Loudspeaker, 100v Transformer	
PX808010	DB14XNG	15 Watt, No labels, 2 x M20 entries, Grey finish	28
		GRP, ATEX Approved Ex II 3GD, EEx nA II T4, zone 2, 100v Transformer,	
PX808401	DB18XNN	15 watt, No labels, 2 x M20 entries, Natural Black finish	5
		Aluminium, ATEX Approved Ex II 3 GD, EEx n II T4, zone 2, 100v Transformer	
PX808501	DB19XW	15 watt projector, No labels, Cable tail, Powder coated to RAL 9010 (White)	0
		GRP, ATEX/IEC Approved Ex de IIC tD A21 T130°C, EExde, IIC 100v Transformer	
PX804301	DB20BC8XNN	8 watt, No labels, 2 x M20 entries Natural Black finish	0
PX804302	DB20BC4XNN	4 watt, No labels, 2 x M20 entries Natural Black finish	11
BELLS			
		Cast Iron, ATEX Approved Ex II 2G, EExd, IIB, T5, Zone 1	
PX806003	DB6BBNR	24v dc, No labels, 2 x M20 entries, 98dB(A) output Painted Red	1
JUNCTION BOXES			
		GRP, ATEX Approved Ex II 2G, EExe IIC, Zone 1 & 2, No labels	
PX810001	JB10BA6NE2B5B8B11BNNN	6xSAK2.5 terms, Earth terminal, Gland continuity, 4xM20 entries, 1 on each face, Natural Black finish	3
		Cast iron body, ATEX Approved Ex II 2G, EExe, IIB T6, Zones 1 & 2, 4xM20 entries 1 per face	
PX820005	8ZE1T1B1R1L11NG	BK6 terminals, painted Grey finish	5
XENON BEACONS			
		GRP body, 60 flashes/min, No labels, IP66 & 67	
PX811101	XB11B02406RNBNNNN	ATEX Approved Ex II 2GD, EExd, IIB, T5, Zone 1 & 2, 5 Joules, 24v, 29Cd, Red lens, Backstrap mounting, 2 x M20 Entries, Black body	1
PX811102	XB11B02406ANBNNNN	ATEX Approved Ex II 2GD, EExd, IIB, T5, Zone 1 & 2, 5 Joules, 24v, 29Cd, Amber lens, Backstrap mounting, 2 x M20 Entries, Black body	1
PX811103	XB11B24006RNBNNNN	ATEX Approved Ex II 2GD, EExd, IIB, T5, Zone 1 & 2, 5 Joules, 240v, 29Cd, Red lens, Backstrap mounting, 2 x M20 Entries, Black body	1
PX811104	XB11B24006ANBNNNN	ATEX Approved Ex II 2GD, EExd, IIB, T5, Zone 1 & 2, 5 Joules, 240v, 29Cd, Amber lens, Backstrap mounting, 2 x M20 Entries, Black body	1
PX813101	XB13024RNNR	Dust-tight & Weatherproof, Uncertified, 10 Joules, 24v d.c., 220 Cd, Red polycarbonate lens, 3 x M20 Entries via knockouts, Red body	5
PX813102	XB13024ANNR	Dust-tight & Weatherproof, Uncertified, 10 Joules, 24v d.c., 220 Cd, Amber polycarbonate lens, 3 x M20 Entries via knockouts, Red body	0
PX813103	XB13230RNNR	Dust-tight & Weatherproof, Uncertified, 10 Joules, 230v a.c., 220 Cd, Red polycarbonate lens, 3 x M20 Entries via knockouts, Red body	1
PX811050	XB10D024FRNN2BN	ATEX Approved Ex II 2G, EExd, IIB, T5, Zone 1 & 2, 15 Joules, 24v, 330Cd, Red lens, Bracket mounting, 2 x M20 Entries, Black body	2
PX811051	XB10D024FANN2BN	ATEX Approved Ex II 2G, EExd, IIB, T5, Zone 1 & 2, 15 Joules, 24v, 330Cd, Amber lens, Bracket mounting, 2 x M20 Entries, Black body	1
PX811052	XB10D240FRNN2BN	ATEX Approved Ex II 2G, EExd, IIB, T5, Zone 1 & 2, 15 Joules, 240v, 330Cd, Red lens, Bracket mounting, 2 x M20 Entries, Black body	1
PX811053	XB10D240FANN2BN	ATEX Approved Ex II 2G, EExd, IIB, T5, Zone 1 & 2, 15 Joules, 240v, 330Cd, Amber lens, Bracket mounting, 2 x M20 Entries, Black body	2
		GRP body ATEX Approved Ex II 2G, EExd, IIB, T4, Zone 1, 2xM20 entries, 60 flashes/min, No labels, Black body	
PX812101	XB12B02406RNBNNNN	21 Joules, 24v, 355Cd, Red lens	0
PX812102	XB12B02406ANBNNNN	21 Joules, 24v, 355Cd, Amber lens	1
PX812103	XB12B24006RNBNNNN	21 Joules, 240v, 355Cd, Red lens	1
PX812104	XB12B24006ANBNNNN	21 Joules, 240v, 355Cd, Amber lens	2

MEDC 24 Hour Stock List

05/03/2010

Shipment of goods on the same day is normally guaranteed when orders are placed before 12 midday.
 Please note that the quantities indicated are changing daily.
 Contact MEDC prior to ordering, if short delivery time is required.
 Please contact Sales department to place your order.
 Tel: +44 (0) 1773 864100

ORDERING CODE	PRODUCT CODE	DESCRIPTION	STOCK LEVEL
		ATEX Approved Ex II 2GD, EExd, IIC, T6, Zone 1 & 2, 2xM20 entries, 60 flashes/min, No labels, Red body	
PX813005	SM87HXBAB024RN1R1LNNR	Alloy, 5 Joules, 24v, 29Cd, Red lens	3
PX813006	SM87HXBAB024AN1R1LNNR	Alloy, 5 Joules, 24v,29Cd, Amber lens	1
PX813007	SM87HXBAB240RN1R1LNNR	Alloy, 7 Joules, 240v,39Cd, Red lens	2
PX813008	SM87HXBAB240AN1R1LNNR	Alloy, 7 Joules, 240v, 39Cd, Amber lens	1
		Alloy, ATEX Approved Ex II 2G, EExd, IIC,T5, Zone 1, 2xM20 entries, 60 flashes/min, No labels, Red body	
PX814001	XB4BB8D2B3B06ANRN1R	21 Joules, 24v, 355Cd, Red lens	1
PX814002	XB4BH8D2B3B06ANRN1R	21 Joules, 240v, 355Cd, Red lens	21
		GRP body, ATEX Approved Ex II 1G, EExia, T4, Zones 0 / 1 / 2 & safe area, Up to 3xM20 entries via knockouts	
PX818002	XB8BB024CNR	24v, IIB, 0.5 Joules, 1 flash/sec, No labels, Clear lens, Red body	2
		GRP body, ATEX Approved Ex II 2G, EExd,T5, Zones 1&2, Natural black body, 1xM20 entry, 60 flash/min, No labels	
PX819105	XB9D02406RYNCBN	5 Joules, 24v, 4.35Cd, Red lens, Lens Guard, S/S mounting bracket, IIC Version	2
PX819106	XB9D02406AYNCBN	5 Joules, 24v, 14.79Cd, Amber lens, Lens Guard, S/S mounting bracket, IIC Version	10
PX819107	XB9D24006RYNCBN	5 Joules, 240v, 4.35Cd, Red lens, Lens Guard, S/S mounting bracket, IIC Version	2
PX819108	XB9D24006AYNCBN	5 Joules, 240v, 14.79Cd, Amber lens, Lens Guard, S/S mounting bracket, IIC Version	1
Dust-tight & Weatherproof Uncertified Products			
BREAKGLASS CALLPOINTS		GRP, 2xM20 entries, Glass label Fire Break Glass, No features, 7 terminals	
PX800006	BG3W1NBR	Dust-tight & weather proof, Uncertified, 24V dc, Duty Label Burning House, Red finish	3
SOUNDERS		GRP, IP66 & 67	
PX808001	DB12P024NR	Dust-tight & Weatherproof, Uncertified, 110 dB(A), 24v dc, No Labels, choice of 27 tones, Red finish	0
PX808003	DB12115NR	Dust-tight & Weatherproof, Uncertified, 115/230v a.c., No Labels, choice of 27 tones, Red finish	4
PX808110	DB15P048NG	Dust-tight & Weatherproof, Uncertified, 117 dB(A), 24-48v dc, 2 x M20 Entries, No labels, Choice of 27 tones, Grey finish	2
PX808115	DB15P048NR	Dust-tight & Weatherproof, Uncertified, 117 dB(A), 24-48v dc, 2 x M20 Entries, No labels, Choice of 27 tones, Painted Red finish	2
PX808120	DB15240NG	Dust-tight & Weatherproof, Uncertified, 117 dB(A), 240v ac, 2 x M20 Entries, Choice of 27 tones, Grey Finish	0
PX808125	DB15240NR	Dust-tight & Weatherproof, Uncertified, 117 dB(A), 240v ac, 2 x M20 Entries, Choice of 27 tones, Red Finish	2
BEACONS		GRP body, 60 flashes/min, No labels, IP66 & 67	
PX813101	XB13024RNNR	Dust-tight & Weatherproof, Uncertified, 10 Joules, 24v d.c., 220 Cd, Red polycarbonate lens, 3 x M20 Entries via knockouts, Red body	5
PX813102	XB13024ANNR	Dust-tight & Weatherproof, Uncertified, 10 Joules, 24v d.c., 220 Cd, Amber polycarbonate lens, 3 x M20 Entries via knockouts, Red body	0
PX813103	XB13230RNNR	Dust-tight & Weatherproof, Uncertified, 10 Joules, 230v a.c., 220 Cd, Red polycarbonate lens, 3 x M20 Entries via knockouts, Red body	1
SPEAKERS		GRP, Industrial & Marine Loudspeaker, 100v Transformer	
PX808010	DB14XNG	15 Watt, No labels, 2 x M20 entries, Grey finish	28